smiths detection

eqo[™] PEOPLE SCREENING TECHNOLOGY



Feature Highlights

- Automatic detection of concealed threats and contraband
- Multi-material detection-reveals any concealed objects such as metals, ceramics, plastics, liquids, narcotics, etc.
- Minimal footprint-allows for easy integration into existing checkpoints
- Instant output of detection results
- Simple scanning procedure– supports rapid processing of people through the checkpoint

eqoTM is an innovative solution to people screening. Using its unique flat-panel millimetre-wave technology this system offers state of the art detection capability within a minimal footprint.

The scanning system provides a rapid means of detecting concealed objects using its real-time automated detection interface.

Instant presentation of the scan result ensures rapid processing and high throughput. Separation of the scanning and alarm resolution further increases the throughput potential.


This 'next-generation' approach marks the evolution of millimetre-wave people screening from mechanically scanned to electronically steered technology, which offers a reliable and easily serviceable system.

The combination of the small footprint and options for right/left panel orientation mean that eqo can be easily integrated into existing checkpoint configurations.

eqo is EU-ECAC Standard 2 approved - already meeting the requirements for aviation installations from 2019 and beyond.

EU ECAC Standard 2 Approved

Detection System	Using active millimetre-wave technology, the flat panel reflect array directs mm-wave energy to and from a person to detect concealed objects.
	Acting as an electronically configurable lens, the panel scans a large cubic volume. This ensures that the person being scanned always remains in focus. The open plan design offers a positive user experience and facilitates ease of communication between the operator and person being screened.
	The operator interface provides instant feedback indicating the location of concealed objects. The output format prompts a directed search for fast alarm resolution.
	Automated checking of the operational process is integrated into the system thus ensuring that the correct screening procedures are implemented.
System Information Scan volume	eqo scans a large three dimensional volume that ensures full coverage of the person being screened.
Detection capability	Objects that the system can detect include but are not limited to: ceramics, metals, liquids, explosives, leather, plastics, paper, narcotics, etc.
Response time	Instantaneous presentation of the detection result
Operating modes	Automated detection for high throughput and high performance detection
	Operator image review for applications where non-standard detection is required
Futures	Scurring Area
Interface control	Responsive touchscreen interface for easy and intuitive operator control with
	minimal training requirements.
Accord	Different levels of passward protected access for apprator supervisors
Access	Different levels of password protected access for operator, supervisors, maintenance technicians, system administrators, etc.
Access	Different levels of password protected access for operator, supervisors, maintenance technicians, system administrators, etc.
	maintenance technicians, system administrators, etc. Combined search/scan for optimum throughput, random alarm generation
	maintenance technicians, system administrators, etc.
Operational Features	maintenance technicians, system administrators, etc. Combined search/scan for optimum throughput, random alarm generation to include additional screening procedures, audio signal alert.
	Combined search/scan for optimum throughput, random alarm generation to include additional screening procedures, audio signal alert. Throughput, scan count, user access, and other operational parameters are
Operational Features	maintenance technicians, system administrators, etc. Combined search/scan for optimum throughput, random alarm generation to include additional screening procedures, audio signal alert.
Operational Features	Combined search/scan for optimum throughput, random alarm generation to include additional screening procedures, audio signal alert. Throughput, scan count, user access, and other operational parameters are
Operational Features Operational data reporting Installation Data	maintenance technicians, system administrators, etc. Combined search/scan for optimum throughput, random alarm generation to include additional screening procedures, audio signal alert. Throughput, scan count, user access, and other operational parameters are automatically recorded by the system 100 VAC - 240 VAC + 10% / -15% • 50 Hz / 60 Hz + 3 Hz (only without UPS) Clearly illustrated location of anomaly
Operational Features Operational data reporting Installation Data Power supply Power consumption	maintenance technicians, system administrators, etc. Combined search/scan for optimum throughput, random alarm generation to include additional screening procedures, audio signal alert. Throughput, scan count, user access, and other operational parameters are automatically recorded by the system 100 VAC - 240 VAC +10% / -15% ◆ 50 Hz / 60 Hz ± 3 Hz (only without UPS) 1.3 KW (nominal) Clearly illustrated location of anomaly objects on the user interface
Operational Features Operational data reporting Installation Data Power supply Power consumption Sound pressure	maintenance technicians, system administrators, etc. Combined search/scan for optimum throughput, random alarm generation to include additional screening procedures, audio signal alert. Throughput, scan count, user access, and other operational parameters are automatically recorded by the system 100 VAC - 240 VAC +10% / -15% • 50 Hz / 60 Hz ± 3 Hz (only without UPS) 1.3 KW (nominal) Clearly illustrated location of anomaly objects on the user interface
Operational Features Operational data reporting Installation Data Power supply Power consumption Sound pressure Dimensions system	maintenance technicians, system administrators, etc. Combined search/scan for optimum throughput, random alarm generation to include additional screening procedures, audio signal alert. Throughput, scan count, user access, and other operational parameters are automatically recorded by the system 100 VAC - 240 VAC +10% / -15% • 50 Hz / 60 Hz ± 3 Hz (only without UPS) 1.3 KW (nominal) < 55 dBA 2415 [L] x 1080 (W) x 2110 (H) [mm] • 95.1" (L) x 42.5" (W) x 83.1" (H)
Operational Features Operational data reporting Installation Data Power supply Power consumption Sound pressure Dimensions system Weight	maintenance technicians, system administrators, etc. Combined search/scan for optimum throughput, random alarm generation to include additional screening procedures, audio signal alert. Throughput, scan count, user access, and other operational parameters are automatically recorded by the system 100 VAC - 240 VAC +10% / -15% • 50 Hz / 60 Hz ± 3 Hz (only without UPS) 1.3 KW (nominal) < 55 dBA 2415 (L) x 1080 (W) x 2110 (H) [mm] • 95.1" (L) x 42.5" (W) x 83.1" (H) <470 kg
Operational Features Operational data reporting Installation Data Power supply Power consumption Sound pressure Dimensions system Weight Storage temperature	maintenance technicians, system administrators, etc. Combined search/scan for optimum throughput, random alarm generation to include additional screening procedures, audio signal alert. Throughput, scan count, user access, and other operational parameters are automatically recorded by the system 100 VAC - 240 VAC +10% / -15% • 50 Hz / 60 Hz ± 3 Hz (only without UPS) 1.3 KW (nominal) < 55 dBA 2415 (L) x 1080 (W) x 2110 (H) [mm] • 95.1" (L) x 42.5" (W) x 83.1" (H) <470 kg -20°C to +60°
Operational Features Operational data reporting Installation Data Power supply Power consumption Sound pressure Dimensions system Weight	maintenance technicians, system administrators, etc. Combined search/scan for optimum throughput, random alarm generation to include additional screening procedures, audio signal alert. Throughput, scan count, user access, and other operational parameters are automatically recorded by the system 100 VAC - 240 VAC +10% / -15% • 50 Hz / 60 Hz ± 3 Hz (only without UPS) 1.3 KW (nominal) < 55 dBA 2415 (L) x 1080 (W) x 2110 (H) [mm] • 95.1" (L) x 42.5" (W) x 83.1" (H) <470 kg -20°C to +60° 0°C to +40°C



For product information, sales or service, please go to www.smithsdetection.com/locations

Altitude > 3 km